

# FAST CLEAN LS12

## Solvent-based metal surface cleaner

**FAST CLEAN LS12** is a fast evaporating, hydrocarbon solvent. It will remove oil and grease from steel and metal parts. It is insoluble in water.

**FAST CLEAN LS12** is more economical in use than chlorinated solvents such as trichloroethylene and is more user friendly because of its lower odour and lower toxicity.

**FAST CLEAN LS12** is highly flammable and should be used in well ventilated areas away from sources of ignition.

### CHEMICAL AND PHYSICAL PROPERTIES

Appearance:	Thin, colourless liquid.
Boiling Point:	50°C
Flash Point:	- 20°C
Density:	0.7
Solubility in water:	Insoluble
Odour:	Low

### DIRECTIONS FOR USE

**FAST CLEAN LS12** can be used as a cleaning solvent by wiping on and wiping off or used in a dip tank with a lid.

### SAFETY

**FAST CLEAN LS12** is a degreaser and will degrease skin so protective clothing should be worn. Solvent vapours can be toxic and the product should only be used in well ventilated areas.

### EFFECT ON MATERIALS OF CONSTRUCTION

**FAST CLEAN LS12** is suitable for use on ferrous, stainless steel, aluminium, brass, copper and most plastic equipment. It may cause some non solvent resistant seals to swell.