

QUICK CLEAN LS1501

Fast Evaporating Solvent Degreaser.

QUICK CLEAN LS1501 is a quick drying degreasing solvent for cleaning machines, metal. It can also be used to remove oil stains on fabric. It can be applied by sprayer, rag, immersion or brush.

QUICK CLEAN LS1501 is based on Heptane which is the safest low boiling point solvent on the market.

QUICK CLEAN LS1501 is highly flammable and should be used in well ventilated areas away from sources of ignition.

CHEMICAL AND PHYSICAL PROPERTIES

Appearance:	Thin, colourless liquid.
Boiling Point:	89 – 95°C
Flash Point:	- 31°C
Density:	0.7
Solubility in water:	Insoluble
Odour:	Low

DIRECTIONS FOR USE

Brush or spray on the greasy surface. Leave for 15 to 30 seconds to allow grease to soften, and then wipe off with a rag or leave to air dry.

SAFETY

QUICK CLEAN LS1501 is a degreaser and will degrease skin so protective clothing should be worn. Solvent vapours can be toxic and the product should only be used in well ventilated areas.

EFFECT ON MATERIALS OF CONSTRUCTION

QUICK CLEAN LS1501 is suitable for use on ferrous, stainless steel, aluminium, brass, copper and most plastic equipment. It may cause some non solvent resistant seals to swell.