

SAFE KLEEN LS10

High Performance Solvent Degreaser

SAFE CLEAN LS10 is a blend of hydrocarbon solvents, and emulsifying agents, formulated to provide excellent penetration and removal of tar, greases and light carbon deposits from metal and non-metal surfaces. It rinses readily and completely from degreased surfaces with either a hot or cold water jet.

SAFE CLEAN LS10 is recommended for use in the mining, transport and engineering industries or whenever a high performance degreaser is required.

SAFE CLEAN LS10 can be used as a parts wash or a slow burning oil for lanterns/wicks with no black smoke residue.

SAFE CLEAN LS10 is DESIGNED:

- to rapidly penetrate, dissolve, emulsify and remove tar, grease and light carbon deposits from a variety of hard surfaces commonly found in the mining, transport, metal working and engineering industries.
- to be corrosion safe on all common metals
- to emulsify dislodged grease and oil, thereby increasing the efficiency of subsequent rinsing operations

CHEMICAL AND PHYSICAL PROPERTIES

Appearance:	Clear, pale colourless liquid
Flash Point:	62°C closed cup
Odour:	Mild hydrocarbon smell
Specific Gravity:	0.8

DIRECTIONS FOR USE

SAFE CLEAN LS10 can be applied by non-atomizing spray, immersion or brush. It should be used cold.

RECOMMENDED CLEANING PROCEDURES:

1. Apply **SAFE CLEAN LS10** by spray, immersion (tank) or brush.
2. Allow 2 minutes to 2 hours for **SAFE CLEAN LS10** to penetrate and dissolve the oil, tar, grease and carbon.
3. Manual agitation if available will reduce the time required for **SAFE CLEAN LS10** to work.

If **SAFE CLEAN LS10** is to be applied by immersion reduce drag-out by allowing sufficient time for drain back into the tank to occur on removal.

1. Rinse with hot or cold water jet.
2. Dry surface with compressed air. If surface is required to self dry, a hot water rinse is recommended

This procedure is provided as a guide only, actually contact time will vary dependent on;

- the nature and quantity of the soil to be removed
- the amount (if any) of mechanical agitation applied

Do **NOT** dilute or contaminate **SAFE CLEAN LS10** with water or pre-wet surface to be cleaned as this will drastically reduce the product's performance.